

TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

Purpose

High-performance, versatile blast cleaning system removes contamination, corrosion, mill scale, and coatings from most surfaces. Produces a uniform surface texture, and creates a surface profile to increase bonding for coatings.

Model 1648 holds 3 cubic feet of abrasive providing 15 minutes of blasting at 100 psi with a No. 6 (3/8-inch) nozzle.

Requirements for Operation

These items are required but not included with this equipment:

- Clean, dry, compressed air of sufficient volume to maintain desired pressure at the nozzle. Refer to Air Consumption Chart in Blast Off 2 booklet (publication stock no. 09294).
- Minimum of 50 psi needed to close the pop-up valve and pressurize the blast machine.
- OSHA-required remote control system that interrupts blasting if operator should lose control of the nozzle when blast machine is pressurized.
- NIOSH-approved, type CE, suppliedair respirator.
- Grade D breathing-air supply as defined by Compressed Gas Association Commodity Specification: G-7.1 (Refer to www.cganet.com).
- Abrasive blast media specifically manufactured for abrasive blasting and appropriate for your application.
- Appropriate blast suit, work boots, hearing and eye protection.

Description

Field-portable, medium-duty, industrial, single-chamber blast machine rated at 150 psi working pressure. Model 1648 has 1-inch piping and holds 3 cubic feet of media (300 lbs expendable, mineral abrasive). This unit is equipped with FSV abrasive metering valve and remote controls. Complete system includes coupled hose, nozzle, supplied air respirator, and many accessories.

3 Cuft Classic Blast Machine Systems with 1" Piping



Description of Operation

The operator controls blasting from a remote control handle at the nozzle. Pressing the handle starts blasting; releasing it stops blasting. The blast machine contains abrasive and meters it into the compressed air stream.


Approvals and Certifications

Blast machine pressure vessel built to American Society of Mechanical Engineers (ASME) specifications for 150-psi working pressure. Vessel is hydrostatically tested and National Board-certified.

Remote control system complies with OSHA regulation 1910.244 (b).

Advantages

- Field-portable, industrial-quality blast machine manufactured to ASME code.
- Industrial-quality valves, piping and fittings designed to maximize air flow and minimize energy required to operate the system.
- FSV abrasive metering valve maintains smooth, consistent, adjustable media flow.
- State-of-the-art NIOSH-approved respirator with DLX comfort-fit suspension.



Model 1648: 3 cuft Blast Machine, Classic with 1" piping; 150 psi working pressure

Item Description	Stock No.	Wt.
Without remotes:		
with FSV abrasive metering	valve	
portable		325
stationary		325
With TLR 100 remotes:		
and FSV abrasive metering	valve	
portable		330
and Manual Quantum meter		
portable		325
and Sentinel abrasive meter		
with ACS (abrasive cut-off		
portable	· · · · · ·	340
stationary		340

Systems

1648-100-CA Includes: 1" piping, Blast ma HP DLX (for use with comp Clem-Cool Air Conditioner (respirator hose, CPF 20 Bre Accessory Package	achine 01178, Apollo ressed air) respirator CCAC), 50 ft.	
1648-ACS-CA		435
Includes: 1" piping, Blast machine 21061,		
Apollo 600 HP DLX respirator with Clem-Cool Air		
Conditioner (CCAC), 50 ft. respirator hose, CPF 20		
Breathing-air filter and Acce	ssory Package	

1648-100-AA**23893** 435 Includes: 1" piping, Blast machine 01178, Apollo 600 LP DLX (for use with ambient air) respirator with Constant Flow Connector (CFC), 50 ft. respirator hose, and Accessory Package

Item Description Stock No. Wt Accessory Package Complete accessory package24194 3 50 ft. x 1" Supa hose w/ NHP-1 and CQPS-123480 30 Blast hose safety cable15013 1.5 1.5 Blast machine screen, 16"03099 6 2 Poly all-weather cover15097 Leather gloves, 1 pair02243 .5 Nylon ties, 8 ea.....02195 <.5 Coupling gaskets, pk of 1021584 .5 NW-25 nozzle washers, pk of 1091024 <.5 Abrasive trap screens, (6)02012 <.5 Helmet outer lenses, pk of 2504361 1 Helmet Int. lenses, pk of 25......24373 2 **Options/Accessories** 6 Blast machine cover, 16".....02335 9 Metering valve, manual Quantum22845 Carbon monoxide alarm, CMS-3 pkg ...24612 4 Ambient Air Pumps CALIPSO, sql operator25908 73 175 CAP-4C, 4 operators w/ cart22384 205 Blast suit, heavy cotton/leather S (08920), M (08921), L (08922), XL (08923), 4.5 (avg.) 2XL (24201), 3XL (24202) Blast suit, seasonal cotton/nylon S (22913), M (22914), L (22915), XL (22916), 2XL (22917), 3XL (25022), 4XL (24689) 3 (avg.) **Operation Manuals** Blast Machine without Remotes06160 Blast Machine with TLR300 Remotes......22501 TLR300 with ACS21260

Sentinel Valve20951

ISO 9001 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.

© 2014 Clemco Industries Corp. • One Cable Car Drive • Washington, MO 63090 • Phone (636) 239-4300 • Fax (800) 726-7559 Stock No. 24581 info@clemcoindustries.com • www.clemcoindustries.com 0513 Rev. A 05/14